

## Laboratory L 2000 series

The L 2000 series is specially designed for storage and transport of liquid nitrogen and is very easy to handle. Lightweight, reliable and robust, the standard L 2000 are fitted with a NW 50 Pneurop flange (except for L 2002, L 2005, L 2012), and planned for the most miscellaneous laboratory and industry applications.

The standard LB 2002 is fitted with a pouring device (to fill nitrogen traps for example).



	<b>LB 2002</b>	<b>L 2002</b>	<b>L 2005</b>	<b>L 2012</b>	<b>L 2025</b>	<b>L 2035</b>	<b>L 2050</b>	<b>L 2100</b>
Capacity (litres)	2	2	5,5	12,4	26	35	50	100
Neck diameter	35	35	50	50	50	50	50	50
Total height (mm)	465	402	494	600	684	591	675	1035
Inner height (mm)	330	330	395	526	611	526	605	922
Outer diameter (mm)	190	190	245	310	395	480	500	500
Empty weight (kg)	2,7	2,7	4,4	8,1	10	13	17	32
Full weight (kg)	4,3	4,3	8,8	18,1	31	41,5	57,5	113
Static consumption (l/day)	/	0,08	0,13	0,14	0,2	0,25	0,3	0,8
NW 50 Pneurop flange	/	Non	Non	Non	Oui	Oui	Oui	Oui
Maximum working pressure (bar)		0,5	0,5	0,5	0,5	0,5	0,5	0,5
Price in EUR	486	390	476	539	649	757	912	1768

